
















List quotation of Shandong Haiyu prestressed pole production line










Tel: 0536-8985335 Fax: 0536-8985335 Mobile: 13853611336
Email: tina@qzhaiyu.com http://qzhyzg.en.alibaba.com

Buyer:	Hu' nan tengda electric power construction co., ltd	Seller:	Shandong Haiyu Heavy Industry Group Co., Ltd.
Telephone:		Telephone:	+86 13853611336
Mailbox:		Mailbox:	tina@qzhaiyu.com
Address:		Address:	Intersection of Zhaode North Road and Rongli Street, Qingzhou Economic Development Zone, Shandong Province

1. equipment list

serial number	device name	picture	weight	parameter			deploy	quantity	unit price	total	remarks
				Length / m	Top diameter / mm	Bottom diameter / mm					
one	Pole mold		5217	17.2	ø228	ø455	High strength bolts are standard	one	¥ 34,777.00	¥ 34,777.00	Running wheel = smooth wheel material: Q235 steel plate thickness: 16mm Wheel material: cast steel mold with holes and pins.
			5251	17.2	ø235	ø462		one	¥ 35,003.00	¥ 35,003.00	
	Tension device		DMZ228-17.2m (9.1+8.1m) Material: Q345			one	¥ 3,650.00	¥ 3,650.00			
			DMZ235-17.2m (9.1+8.1m) Material: Q345			one	¥ 3,650.00	¥ 3,650.00			
2	centrifuge		11500kg	Model: LG-8-(150-350)×15 Through shaft diameter: 125mm through shaft material: 45# Roller diameter: 600mm Roller thickness: ≥ 50 mm. Effective width of wheel surface: ≥95mm Bearing model: 22228CAK Material of roller of centrifuge: ZG40Mn2 steel casting flange thickness and quantity: 30mm/8 pieces. Connection mode of flange and idler: integral center distance between two shafts: 950 mm. Centrifuge base material: ZG35 Overall dimensions: 17500×1600×720mm.			Article 1	¥127,500.00	¥127,500.00		
				6-45KW variable frequency motor 55KW control cabinet			1 set	¥19,650.00	¥19,650.00		
three	forced mixer		5000kg	Model: JS750 discharge capacity: 750L feed capacity: 1200L Productivity: ≥ 35m/h Mixing motor: 30kw winding motor: 7.5kw water pump motor: 1.1kw Hopper lifting speed: 19m/min discharging height: 2600mm. Overall dimensions: 3000×2200×2500mm			1 set	¥60,000.00	¥60,000.00	Forced/twin turbines	
four	Sancang dosing machine		3500kg	Model: PLD1200 weighing hopper capacity: 1200L storage hopper capacity: 3×3m³ Productivity: 60m/h batching accuracy: 2% Maximum weighing value: 3000kg Ingredients: 3 kinds Feeding height: 2430mm Motor power: 3kw×3/4kw×1 Overall dimensions: 8800×1900×2400 mm.			1 set	¥36,000.00	¥36,000.00	Sancang	
five	Cement weighing		90kg	Measurement accuracy of cement measuring hopper: 2 Measuring range: ≤250kg Unloading mode: pneumatic butterfly valve. Sensor: CDLG-1(300kg)			1 set	¥8,500.00	¥8,500.00	Cement measurement	
six	Shuicheng		90kg	Metering accuracy of water metering hopper: 2 Maximum water volume: 200kg Sensor: CDLG-1(300kg)			1 set	¥8,500.00	¥8,500.00	Water metering	
				Model: SNC100 capacity: 100T/83 cubic bin diameter:							

nine	mechanical loader		6990kg	<p>Model: 936N Rated load: 2000kg Rated power: 85kw Standard bucket capacity: 1.2m³ Unloading height: 3200mm; maximum digging force: 100KN; maximum speed: 25km/h. Engine model: YN4EL120 Overall dimensions: 6350×2200×3000mm.</p>	1 vehicle	¥115,000.00	¥115,000.00	raw material
10	Cloth machine		933kg	<p>Model: FM1000 feeding motor: 4kw walking motor: 1.5kw hopper capacity: 1000L Mixing cage diameter: 320mm running speed: 13.69m/min running wheel diameter: φ310mm running wheel track: 936mm Control mode: wireless remote control. Cable drum: AC380V3×2.5+1×1.5 Overall dimensions: 2000×1700×2100mm</p>	1 set	¥20,000.00	¥20,000.00	Cable drum
			24kg	P24 track+connecting plate+connecting bolt	40 meters	¥150.00	¥6,000.00	
				3×2.5 stay cable	30 meters	¥20.00	¥600.00	
11	steam boiler		4190kg	<p>Model: WNS1-1.0-Y(Q) Rated evaporation: 1t/h Rated steam pressure: 1.0MPa Steam temperature: 194°C Design thermal efficiency: 91.52% Installed capacity: 3.15kw. Available fuel: light oil/heavy oil/natural gas. Light oil consumption: 69.36kg/h. Natural gas consumption: 84.33Nm³/h Overall dimensions: 2800×1650×1800mm m.</p>	1 set	¥65,000.00	¥65,000.00	steam curing
				TBL85P Italian Baide burner	1 set	¥14,000.00	¥14,000.00	
				Touch screen boiler control cabinet	1 set	¥7,000.00	¥7,000.00	
				KQDP25-2S×16 make-up pump	2 sets	¥3,500.00	¥7,000.00	Shanghai Kaiquan
				meter valve	1 set	¥7,500.00	¥7,500.00	
				φ300mm×8m chimney	1 set	¥3,000.00	¥3,000.00	
				1T full-automatic two-stage softening water treatment equipment	1 set	¥3,000.00	¥3,000.00	With three sets of soft water salt+
				1M3 daily fuel tank	one	¥3,000.00	¥3,000.00	
				3m ³ daily water tank	one	¥5,000.00	¥5,000.00	
				φ219mm cylinder with one inlet and four outlets.	1 set	¥2,640.00	¥2,640.00	
	Install accessories, pipes, thermometers and on-off valves.	4 sets	¥1,500.00	¥6,000.00				
twelve	Tension machine		320kg	<p>Model: ZB6-600 Oil pump revolution: 1440r/min Tension trolley /YCW200D jack (upper lifting) Nominal oil pressure: 53MPa Tensile force: 2007KN Tension piston area: 3.788×10-2m². Return piston area: 2.17×10-2m². Tension stroke: 200mm.</p>	1 set	¥30,000.00	¥30,000.00	
13	Steel clip			<p>Aperture: 5.2mm Material: Q345B</p>	1000	¥4.00	¥4,000.00	
14	Open pier head device		248kg	<p>Model: SHD-DT Rated pressure: 16Mpa Heading diameter: 6~9mm Applicable reinforcement type: high-strength reinforcement Maximum pier head force: 46T Upsetting speed: 5s/piece. Power: 3kw Overall dimensions: 637×580×917mm</p>	2 sets	¥15,000.00	¥30,000.00	
15	Erection and vertical looping machine		400kg	<p>Model: DQ1000K Power: 2.2kw Accuracy: ±0.5mm Speed: 15m/min Wire diameter: 2~6mm Ring diameter: 80~1000mm. Overall dimensions: 1300×700×1470mm</p>	1 set	¥20,000.00	¥20,000.00	Prestressed equipment
			30kg	Pay-off movable disc	2 sets	¥1,200.00	¥2,400.00	
16	Pneumatic spot welder		260kg	<p>Model: UN25Q Power: 25KVA Voltage: 380V/50HZ Maximum clamping force: 500kgf Maximum upsetting force: 250kgf. Steel wire diameter: 2.0-6mm Gas consumption: 150L/MIN. Transformer design power: 40KVA Working load: 15KVA Overall dimensions: 700×480×930mm.</p>	1 set	¥18,000.00	¥18,000.00	
17	Outer ring rib winding machine		100kg	<p>Model: WM1000 Motor: 1.5kw Speed ratio of reducer: 17 Minimum winding diameter: 140mm. Maximum winding diameter: 270mm Overall dimensions: 1400×750×860mm.</p>	1 set	¥9,000.00	¥9,000.00	
18	High strength wire fixed length cutter		1600kg	<p>Model: GQ4-7 Diameter of cut steel bar: φ 4.8 φ 7.0mm. Length of cut steel bar: 5000-15000mm. Air source: 7.2kg/cm² Maximum cutting force: 13T</p>	1 set	¥53,000.00	¥53,000.00	

				<p>Cutting error: 1 mm Maximum traction speed: 64m/min Input voltage: AC 380 V 5%, 50Hz. Overall dimensions: 17000×700×2100mm</p>				
19	Single beam bridge crane		5500kg	<p>Model: LDE5t+5t Lifting weight: 10t Span: 20m Lifting height: 9m Rated power: 19.6kw Lifting speed: 8m/min. Hoist running speed: 20m/min cart running speed: 30m/min cart wheel diameter: 300mm Operation mode: remote control. Work level: A4</p>	2 sets	¥82,162.00	¥164,324.00	Used in production workshop
				P24 track+connecting plate+connecting bolt	120 meters	¥150.00	¥18,000.00	
				P24 welding pressure plate (2 pieces/1m)	120 meters	¥15.00	¥1,800.00	
				3×30 seamless sliding contact line	60 meters	¥85.00	¥5,100.00	
twenty	Single-beam gantry crane		12000kg	<p>Model: MH5t×32m Lifting weight: 5t Span: 32m Lifting height: 7m Rated power: 10.9kw Lifting speed: 8m/min. Hoist running speed: 20m/min cart running speed: 30m/min cart wheel diameter: 300mm Operation mode: remote control. Work level: A4</p>	1 set	¥130,000.00	¥130,000.00	Used in outdoor storage yard
			24kg	P24 track+connecting plate+connecting bolt	120 meters	¥150.00	¥18,000.00	
				P24 welding pressure plate (2 pieces/1m)	120 meters	¥15.00	¥1,800.00	
				3×30 seamless sliding contact line	60 meters	¥85.00	¥5,100.00	
21	Rod carrier		1000kg	<p>Model: BJT-3 rated load: 3T Wheel diameter: 300mm Number of wheels: 4 Motor power: 1.5kw running speed: 0-20m/min track center distance: 700mm. Cable drum: AC380V3×2.5+1×1.5 Length of stay cable: 35M Control mode: remote control. Overall dimensions: 6000×1000×520mm</p>	1 vehicle	¥24,500.00	¥24,500.00	
			24kg	P24 track+connecting plate+connecting bolt	40 meters	¥180.00	¥7,200.00	
22	Hoisting tool			Finished pole grab hook	two	¥1,200.00	¥2,400.00	Hoisting tools for production
				5T/6M lifting belt	four	¥180.00	¥720.00	
				5t suspension chain	10 meters	¥65.00	¥650.00	
				5t butterfly buckle	16	¥75.00	¥1,200.00	
				5t hook	eight	¥100.00	¥800.00	
				5t O ring	four	¥70.00	¥280.00	
23	Permanent magnet variable frequency screw air compressor		265kg	<p>Model: AT-30PM power: 22kw Exhaust volume: 3.56m³/min exhaust pressure: 0.8Mpa cooling mode: air cooling. Drive mode: direct connection start mode: soft start Overall dimensions: 1000×750×1140mm.</p>	1 set	¥18,000.00	¥18,000.00	Permanent magnet frequency conversion technology, saving energy and electricity. Famous brands in the industry
24	air tank		440kg	<p>Working pressure: 0.84 Mpa void volume: 1000L. Cylinder thickness: 5mm Design temperature: 150 C. Size: φ820×2280mm</p>	1 set	¥2,000.00	¥2,000.00	
25	freeze drier			<p>Model: CY-30AC Air treatment: 3.8m³/min voltage: 220V/50HZ. Power: 1.1kw Working pressure: ≤1.0Mpa Refrigerant: R22A Overall dimensions: 930×480×880mm.</p>	1 set	¥3,500.00	¥3,500.00	
				ATC013 precision filter (with automatic internal discharge)	three	¥450.00	¥1,350.00	
				High pressure tubing and fittings	1 set	¥1,000.00	¥1,000.00	
26	Pneumatic wrench		9kg	<p>Model: 4800 Applicable bolt: M30 Maximum torque: 2150N.M No-load speed: 4000~5000r/min 30 # sleeve</p>	4 bars	¥1,600.00	¥6,400.00	Used to open and close the mold
				Special windpipe for wind cannon (20M/plate)	eight	¥81.00	¥648.00	
				Special windpipe for wind cannon (20M/plate)	4 sets	¥340.00	¥1,360.00	
				Quick connector	four	¥75.00	¥300.00	
27	total						¥1,257,802.00	

- Remarks: 1. Quotation time: July 9, 2024;
2. This quotation includes 13% value-added tax, excluding transportation expenses.
3. The design maximum single length is 15M.
4. If the customer provides the factory floor plan, our company can provide the PDF version of the factory layout plan for free.
5. This production line can normally produce 4-5 poles per hour;

Zhang Wenwen:
13853611336
Shandong Haiyu Heavy Industry Group Co., Ltd.